



RICARDO DIESEL GENSET

TMG-R 110

GROUP Standby Power Prime Power

Power	kVA	110	100	
Power	kW	88	80	
Engine Speed	rpm	1500		
Standard Voltage	V	400 / 230		
Power Factor	Cos Phi	0,8		

Standby Power The maxpower available

Continuous Power

tor must not be overloaded.

The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load. Average load can be 100%. The genera-

Prime Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.



Mermerciler Sanayi Sitesi 3. Cadde No: 7 / B Beylikduzu / ISTANBUL / TURKEY

www.tmgpower.com.tr





TMG-R 110


Engine Properties


Brand Model		Ricardo
Model		
		R 6105ZD
Medicine		Direct Injection
Standby Power	kW	88
Prime Power	kW	80
Cylinder Volume	lt.	5,13
Number of Cylinders / Type		6 - Sıra
Engine Speed	rpm	1500
Aspiration		Natural Suction
Cooling Type		Water Radiator
Heater Power		1000V
Cycle / Minutes		1500
Piston Diameter And Stroke	mmxmm	110X135
Governor Class		Mechanic
Fuel Consumption 100%	lt.	21,8
Fuel Consumption% 50	lt.	10,9
Oil Capacity	lt.	16
Water Capacity	lt.	25
Voltage	V	12V
Battery Capacity	Α	105A

Alternator Properties

Output Voltage	V	230/400
Frequency	HZ	50
Automatic Voltage Regulation	±%	0,5
Stand by Power	kVA	110
Prime Power	kVA	88
Power Factor	Cosq	0,8
Number of Cables		12
Winding Line		2/3
Protection Class		IP23 / H
Warning System		Self-Alert
AVR Model		SX460
Alternator Efficiency	%	92

Diemensions





Canopied

LxWxH	mm	2650x950x1860
Weight	kg	1404
Fuel Tank Capacity	lt.	165

Open Set

LxWxH	mm	2350x950x1460
Weight	kg	1070
Fuel Tank Capacity	lt.	165

Optitonal

Some Optional Equipments that TMG POWER provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Remote monitoring.
- SMPS 12/24V 10A

Kontrol Panel

- Datakom D500
- Datakom D700
- ComAp AMF9
- ComAp AMF25

TMG POWER