



RICARDO DIESEL GENSET

| GROUP | | Standby Power | Prime Power | | |
|------------------|---------|---------------|-------------|--|--|
| Power | kVA | 225 | 205 | | |
| Power | kW | 180 | 164 | | |
| Engine Speed | rpm | 1500 | | | |
| Standard Voltage | V | 400 / 230 | | | |
| Power Factor | Cos Phi | 0,8 | | | |



TMG-R 220

Continuous Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

Standby Power


The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Mermerciler Sanayi Sitesi 3. Cadde No: 7 / B Beylikduzu / ISTANBUL / TURKEY

www.tmgpower.com.tr







TMG-R 220


Engine Properties


| Brand | | Ricardo |
|----------------------------|-------|------------------|
| Model | | R 6113ZLD |
| Medicine | | Direct Injection |
| Standby Power | kW | 170 |
| Prime Power | kW | 154 |
| Cylinder Volume | lt. | 7,7 |
| Number of Cylinders / Type | | 6 - Sıra |
| Engine Speed | rpm | 1500 |
| Aspiration | | Natural Suction |
| Cooling Type | | Water Radiator |
| Heater Power | | 1000V |
| Cycle / Minutes | | 1500 |
| Piston Diameter And Stroke | ттхтт | 110x135 |
| Governor Class | | Mechanic |
| Fuel Consumption 100% | lt. | 40 |
| Fuel Consumption% 50 | lt. | 19,9 |
| Oil Capacity | lt. | 22 |
| Water Capacity | lt. | 35 |
| Voltage | V | 12V |
| Battery Capacity | А | 105A |
| | | |

Alternator Properties

| V | 230/400 | | |
|------|--------------------------------|--|--|
| ΗZ | 50 | | |
| ±% | 0,5 | | |
| kVA | 225 | | |
| kVA | 180 | | |
| Cosq | 0,8 | | |
| | 12 | | |
| | 2/3 | | |
| | IP23 / H | | |
| | Self-Alert | | |
| | SX460 | | |
| % | 92 | | |
| | HZ ±% kVA KVA Cosq | | |

Diemensions





Open Set

| LxWxH | mm | 3070x1100x2000 | LxWxH | mm | 2770x1100x1600 |
|--------------------|-----|----------------|--------------------|-----|----------------|
| Weight | kg | 1855 | Weight | kg | 1460 |
| Fuel Tank Capacity | lt. | 304 | Fuel Tank Capacity | lt. | 304 |

Optitonal

Some Optional Equipments that TMG POWER provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Remote monitoring.
- SMPS 12/24V 10A

Kontrol Panel

- Datakom D500
- Datakom D700
- ComAp AMF9
- ComAp AMF25

Mermerciler Sanayi Sitesi 3. Cadde No: 7 / B Beylikduzu / ISTANBUL / TURKEY

www.tmgpower.com.tr



+90 212 641 94 21 | info@tmgpower.com.tr