



## **RICARDO DIESEL GENSET**

GROUP		Standby Power	Prime Power		
Power	kVA	300	270		
Power	kW	240	216		
Engine Speed	rpm	1500			
Standard Voltage	V	400 / 230			
Power Factor	Cos Phi	0,8			



## TMG-R 300

## **Continuous Power**

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

## **Standby Power**


The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

## **Prime Power**

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Mermerciler Sanayi Sitesi 3. Cadde No: 7 / B Beylikduzu / ISTANBUL / TURKEY

www.tmgpower.com.tr







# **TMG-R 300**


## **Engine Properties**


Brand		Ricardo
Model		R 6126ZLD
Medicine		Direct Injection
Standby Power	kW	260
Prime Power	kW	236
Cylinder Volume	lt.	
Number of Cylinders / Type		6 - Sıra
Engine Speed	rpm	1500
Aspiration		Natural Suction
Cooling Type		Water Radiator
Heater Power		1000V
Cycle / Minutes		1500
Piston Diameter And Stroke	mmxmm	126x130
Governor Class		Mechanic
Fuel Consumption 100%	lt.	53
Fuel Consumption% 50	lt.	26
Oil Capacity	lt.	19
Water Capacity	lt.	50
Voltage	V	12V
Battery Capacity	А	105A

## **Alternator Properties**

Output Voltage	V	23+029:P350/400		
Frequency	ΗZ	50		
Automatic Voltage Regulation	±%	0,5		
Stand by Power	kVA	300		
Prime Power	kVA	240		
Power Factor	Cosq	0,8		
Number of Cables		12		
Winding Line		2/3		
Protection Class		IP23 / H		
Warning System		Self-Alert		
AVR Model		SX460		
Alternator Efficiency	%	92		

### **Diemensions**





#### **Open Set**

L x W x H	mm	3680x1200x2000	LxWxH	mm	3380x1200x1600
Weight	kg	2200	Weight	kg	1720
Fuel Tank Capacity	lt.	368	Fuel Tank Capacity	lt.	368

### **Optitonal**

Some Optional Equipments that TMG POWER provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Remote monitoring.
- SMPS 12/24V 10A

#### Kontrol Panel

- Datakom D500
- Datakom D700
- ComAp AMF9
- ComAp AMF25

## Mermerciler Sanayi Sitesi 3. Cadde No: 7 /B Beylikduzu / ISTANBUL / TURKEY

#### www.tmgpower.com.tr



+90 212 641 94 21 | info@tmgpower.com.tr