



RICARDO DIESEL GENSET

TMG-R 75

GROUP Standby Power Prime Power

Power	kVA	77	70
Power	kW	61	56
Engine Speed	rpm	1500	
Standard Voltage	V	400 / 230	
Power Factor	Cos Phi	0,8	

Continuous Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

Standby Power

The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.



Mermerciler Sanayi Sitesi 3. Cadde No: 7 / B Beylikduzu / ISTANBUL / TURKEY

www.tmgpower.com.tr





TMG-R75


Engine Properties


Brand		Ricardo
Model		R ZH 4105ZD
Medicine		Direct Injection
Standby Power	kW	61
Prime Power	kW	56
Cylinder Volume	lt.	4,33
Number of Cylinders / Type		4 - Sıra
Engine Speed	rpm	1500
Aspiration		Natural Suction
Cooling Type		Water Radiator
Heater Power		1000V
Cycle / Minutes		1500
Piston Diameter And Stroke	mmxmm	105x125
Governor Class		Mechanic
Fuel Consumption 100%	lt.	14,3
Fuel Consumption% 50	lt.	7,01
Oil Capacity	lt.	14
Water Capacity	lt.	21
Voltage	V	12V
Battery Capacity	А	105A

Alternator Properties

Output Voltage	V	230/400
Frequency	HZ	50
Automatic Voltage Regulation	±%	0,5
Stand by Power	kVA	75
Prime Power	kVA	60
Power Factor	Cosq	0,8
Number of Cables		12
Winding Line		2/3
Protection Class		IP23 / H
Warning System		Self-Alert
AVR Model		SX460
Alternator Efficiency	%	92

Diemensions





Canopied

LxWxH	mm	2650x950x1860
Weight	kg	1284
Fuel Tank Capacity	lt.	165

Open Set

LxWxH	mm	2350x950x1460
Weight	kg	982
Fuel Tank Capacity	lt.	165

Optitonal

Some Optional Equipments that TMG POWER provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Remote monitoring.
- SMPS 12/24V 10A

Kontrol Panel

- Datakom D500
- Datakom D700
- ComAp AMF9
- ComAp AMF25

TMG POWER